



**DECLARATION OF PERFORMANCE**  
No-Sikla-1.1-101  
REGULATION (EU) No 305/2011

EN

|  |   |
|--|---|
| Unique identification code of the product-type | <b>Wedge Anchor AN BZ plus and AN BZ-IG</b>                               |
| Intended use                                   | Mechanical fastener for use in concrete, see Annex B                      |
| Manufacturer                                   | Sikla Holding GmbH<br>Ägydiplatz 3<br>4600 Thalheim bei Wels - Österreich |
| System of AVCP                                 | System 1  |
| European Assessment Document:                  | EAD 330232-01-0601 Edition 05/2021  |
| European Technical Assessment                  | ETA-10/0259, 10.01.2023   |
| Technical Assessment Body                      | DIBt, Berlin  |
| Notified body                                  | Technische Universität Darmstadt - NB 2873                                |

| Essential characteristics  | Performance  |
|--|--|
| <b>Mechanical resistance and stability (BWR 1)</b>                                     |  |
| Characteristic resistance to tension load (static and quasi-static loading)            | AN BZ plus: Annex B4, B5, C1-C4<br>AN BZ-IG: Annex B8, C11-C12 |
| Characteristic resistance to shear load (static and quasi-static loading)              | AN BZ plus: Annex C5<br>AN BZ-IG: Annex C13                    |
| Displacements (static and quasi-static loading)  | AN BZ plus: Annex C9-C10<br>AN BZ-IG: Annex C15                |
| Characteristic resistance and displacements for seismic performance category C1 and C2 | AN BZ plus: Annex C6, C9-C10<br>AN BZ-IG: NPD                  |
| <b>Safety in case of fire (BWR 2)</b>  |  |
| Reaction to fire   | Class A1   |
| Resistance to fire   | AN BZ plus: Annex C7-C8<br>AN BZ-IG: Annex C14                 |
| <b>Aspects of durability</b>   |  |
| Durability   | Annex B1   |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Villingen-Schwenningen, 20.02.2023



Günter Brugger | Head of IPRM



Achim Münch | Head of QM

The original of this declaration of performance was written in German. In the event of deviations in the translation, the German version shall be valid.

## Specifications of intended use

| Wedge Anchor AN BZ plus                                   |    |     |     |     |     |     |     |
|---|----|-----|-----|-----|-----|-----|-----|
| Standard anchorage depth                                  | M8 | M10 | M12 | M16 | M20 | M24 | M27 |
| Steel, galvanized   |    |     |     | ✓   |     |     |     |
| Steel, sherardized  |    |     |     | ✓   |     |     |     |
| Stainless steel A4 and high corrosion resistant steel HCR |    |     | ✓   |     |     |     | _2) |
| Static or quasi-static action                             |    |     |     | ✓   |     |     |     |
| Fire exposure   |    |     |     | ✓   |     |     |     |
| Seismic action (C1 and C2) <sup>1)</sup>                  |    |     | ✓   |     |     | _2) | _2) |
| Reduced anchorage depth <sup>1)</sup>                     | M8 | M10 | M12 | M16 |     |     |     |
| Steel, galvanized   |    | ✓   |     |     |     |     |     |
| Steel, sherardized  |    | ✓   |     |     |     |     |     |
| Stainless steel A4 and high corrosion resistant steel HCR |    | ✓   |     |     |     |     |     |
| Static or quasi-static action                             |    | ✓   |     |     |     |     |     |
| Fire exposure   |    | ✓   |     |     |     |     |     |
| Seismic action (C1 and C2)                                |    |     | _2) |     |     |     |     |

<sup>1)</sup> Only cold formed anchors acc. to Annex A3

<sup>2)</sup> No performance assessed

| Wedge Anchor AN BZ-IG                                     | M6 | M8 | M10 | M12 |
|---|----|----|-----|-----|
| Steel, galvanized   |    |    | ✓   |     |
| Stainless steel A4 and high corrosion resistant steel HCR |    |    | ✓   |     |
| Static or quasi-static action                             |    |    | ✓   |     |
| Fire exposure   |    |    | ✓   |     |
| Seismic action (C1 and C2)                                |    |    | _1) |     |

<sup>1)</sup> No performance assessed

### Base materials:

- Compacted, reinforced or unreinforced normal weight concrete (without fibers) according to EN 206:2013+A1:2016
- Strength classes C20/25 to C50/60 according to EN 206:2013+A1:2016
- Cracked or uncracked concrete

### Use conditions (Environmental conditions):

- Structures subject to dry internal conditions: all materials
- For all other conditions: Intended use of materials according to Annex A4, Table A2 or Annex A7, Table A4 corresponding corrosion resistance classes CRC according to EN 1993-1-4:2006+A1:2015

## SIKLA Wedge Anchor AN BZ plus and AN BZ-IG

Intended use  
Specifications

Annex B1

**Table B2: Minimum spacings and edge distances, standard anchorage depth, AN BZ plus**

| Fastener size                                     |              |      | M8                             | M10 | M12 | M16 | M20             | M24             | M27             |
|---|--------------|------|--------------------------------|-----|-----|-----|-----------------|-----------------|-----------------|
| <b>Standard thickness of concrete member</b>      |              |      |                                |     |     |     |                 |                 |                 |
| <b>Steel zinc plated</b>                          |              |      |                                |     |     |     |                 |                 |                 |
| Standard thickness of member                      | $h_{min,1}$  | [mm] | 100                            | 120 | 140 | 170 | 200             | 230             | 250             |
| <b>Cracked concrete</b>                           |              |      |                                |     |     |     |                 |                 |                 |
| Minimum spacing                                   | $S_{min}$    | [mm] | 40                             | 45  | 60  | 60  | 95              | 100             | 125             |
|   | für $c \geq$ | [mm] | 70                             | 70  | 100 | 100 | 150             | 180             | 300             |
| Minimum edge distance                             | $C_{min}$    | [mm] | 40                             | 45  | 60  | 60  | 95              | 100             | 180             |
|   | für $s \geq$ | [mm] | 80                             | 90  | 140 | 180 | 200             | 220             | 540             |
| <b>Uncracked concrete</b>                         |              |      |                                |     |     |     |                 |                 |                 |
| Minimum spacing                                   | $S_{min}$    | [mm] | 40                             | 45  | 60  | 65  | 90              | 100             | 125             |
|   | für $c \geq$ | [mm] | 80                             | 70  | 120 | 120 | 180             | 180             | 300             |
| Minimum edge distance                             | $C_{min}$    | [mm] | 50                             | 50  | 75  | 80  | 130             | 100             | 180             |
|   | für $s \geq$ | [mm] | 100                            | 100 | 150 | 150 | 240             | 220             | 540             |
| <b>Stainless steel A4, HCR</b>                    |              |      |                                |     |     |     |                 |                 |                 |
| Standard thickness of member                      | $h_{min,1}$  | [mm] | 100                            | 120 | 140 | 160 | 200             | 250             | - <sup>1)</sup> |
| <b>Cracked concrete</b>                           |              |      |                                |     |     |     |                 |                 |                 |
| Minimum spacing                                   | $S_{min}$    | [mm] | 40                             | 50  | 60  | 60  | 95              | 125             | - <sup>1)</sup> |
|   | für $c \geq$ | [mm] | 70                             | 75  | 100 | 100 | 150             | 125             |                 |
| Minimum edge distance                             | $C_{min}$    | [mm] | 40                             | 55  | 60  | 60  | 95              | 125             |                 |
|   | für $s \geq$ | [mm] | 80                             | 90  | 140 | 180 | 200             | 125             |                 |
| <b>Uncracked concrete</b>                         |              |      |                                |     |     |     |                 |                 |                 |
| Minimum spacing                                   | $S_{min}$    | [mm] | 40                             | 50  | 60  | 65  | 90              | 125             | - <sup>1)</sup> |
|   | für $c \geq$ | [mm] | 80                             | 75  | 120 | 120 | 180             | 125             |                 |
| Minimum edge distance                             | $C_{min}$    | [mm] | 50                             | 60  | 75  | 80  | 130             | 125             |                 |
|   | für $s \geq$ | [mm] | 100                            | 120 | 150 | 150 | 240             | 125             |                 |
| <b>Minimum thickness of concrete member</b>       |              |      |                                |     |     |     |                 |                 |                 |
| <b>Steel zinc plated, stainless steel A4, HCR</b> |              |      |                                |     |     |     |                 |                 |                 |
| Minimum thickness of member                       | $h_{min,2}$  | [mm] | 80                             | 100 | 120 | 140 | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
| <b>Cracked concrete</b>                           |              |      |                                |     |     |     |                 |                 |                 |
| Minimum spacing                                   | $S_{min}$    | [mm] | 40                             | 45  | 60  | 70  | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
|   | für $c \geq$ | [mm] | 70                             | 90  | 100 | 160 |                 |                 |                 |
| Minimum edge distance                             | $C_{min}$    | [mm] | 40                             | 50  | 60  | 80  |                 |                 |                 |
|   | für $s \geq$ | [mm] | 80                             | 115 | 140 | 180 |                 |                 |                 |
| <b>Uncracked concrete</b>                         |              |      |                                |     |     |     |                 |                 |                 |
| Minimum spacing                                   | $S_{min}$    | [mm] | 40                             | 60  | 60  | 80  | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
|   | für $c \geq$ | [mm] | 80                             | 140 | 120 | 180 |                 |                 |                 |
| Minimum edge distance                             | $C_{min}$    | [mm] | 50                             | 90  | 75  | 90  |                 |                 |                 |
|   | für $s \geq$ | [mm] | 100                            | 140 | 150 | 200 |                 |                 |                 |
| <b>Fire exposure from one side</b>                |              |      |                                |     |     |     |                 |                 |                 |
| Minimum spacing                                   | $S_{min,fi}$ | [mm] | See normal ambient temperature |     |     |     |                 |                 |                 |
| Minimum edge distance                             | $C_{min,fi}$ | [mm] | See normal ambient temperature |     |     |     |                 |                 |                 |
| <b>Fire exposure from more than one side</b>      |              |      |                                |     |     |     |                 |                 |                 |
| Minimum spacing                                   | $S_{min,fi}$ | [mm] | See normal ambient temperature |     |     |     |                 |                 |                 |
| Minimum edge distance                             | $C_{min,fi}$ | [mm] | $\geq 300$ mm                  |     |     |     |                 |                 |                 |

Intermediate values by linear interpolation.

<sup>1)</sup> No performance assessed

**SIKLA Wedge Anchor AN BZ plus**

**Intended use**  
Minimum spacings and edge distances for standard anchorage depth

**Annex B4**

**Table B3: Minimum spacings and edge distances, reduced anchorage depth, AN BZ plus**

| Fastener size                                |                   | M8                             | M10 | M12 | M16 |
|--|-------------------|--------------------------------|-----|-----|-----|
| Minimum thickness of concrete member         | $h_{min,3}$ [mm]  | 80                             | 80  | 100 | 140 |
| <b>Cracked concrete</b>                      |                   |                                |     |     |     |
| Minimum spacing                              | $s_{min}$ [mm]    | 50                             | 50  | 50  | 65  |
|  | für $c \geq$ [mm] | 60                             | 100 | 160 | 170 |
| Minimum edge distance                        | $c_{min}$ [mm]    | 40                             | 65  | 65  | 100 |
|  | für $s \geq$ [mm] | 185                            | 180 | 250 | 250 |
| <b>Uncracked concrete</b>                    |                   |                                |     |     |     |
| Minimum spacing                              | $s_{min}$ [mm]    | 50                             | 50  | 50  | 65  |
|  | für $c \geq$ [mm] | 60                             | 100 | 160 | 170 |
| Minimum edge distance                        | $c_{min}$ [mm]    | 40                             | 65  | 100 | 170 |
|  | für $s \geq$ [mm] | 185                            | 180 | 185 | 65  |
| <b>Fire exposure from one side</b>           |                   |                                |     |     |     |
| Minimum spacing                              | $s_{min,fi}$ [mm] | See normal ambient temperature |     |     |     |
| Minimum edge distance                        | $c_{min,fi}$ [mm] | See normal ambient temperature |     |     |     |
| <b>Fire exposure from more than one side</b> |                   |                                |     |     |     |
| Minimum spacing                              | $s_{min,fi}$ [mm] | See normal ambient temperature |     |     |     |
| Minimum edge distance                        | $c_{min,fi}$ [mm] | $\geq 300$ mm                  |     |     |     |

Intermediate values by linear interpolation.

**SIKLA Wedge Anchor AN BZ plus**

**Intended use**  
Minimum spacings and edge distances for reduced anchorage depth

**Annex B5**

**Table B4: Installation parameters AN BZ-IG**

| Fastener size                                   |                    |         | M6   | M8    | M10  | M12  |
|---|--------------------|---------|------|-------|------|------|
| Effective anchorage depth                       | $h_{ef}$           | [mm]    | 45   | 58    | 65   | 80   |
| Drill hole diameter                             | $d_0$              | [mm]    | 8    | 10    | 12   | 16   |
| Cutting diameter of drill bit                   | $d_{cut} \leq$     | [mm]    | 8,45 | 10,45 | 12,5 | 16,5 |
| Depth of drill hole                             | $h_1 \geq$         | [mm]    | 60   | 75    | 90   | 105  |
| Screwing depth of threaded rod                  | $L_{sd}^{2)} \geq$ | [mm]    | 9    | 12    | 15   | 18   |
| Installation torque,<br>steel zinc plated       | $T_{inst}$         | S [Nm]  | 10   | 30    | 30   | 55   |
|   |                    | SK [Nm] | 10   | 25    | 40   | 50   |
|   |                    | B [Nm]  | 8    | 25    | 30   | 45   |
| Installation torque,<br>stainless steel A4, HCR | $T_{inst}$         | S [Nm]  | 15   | 40    | 50   | 100  |
|   |                    | SK [Nm] | 12   | 25    | 45   | 60   |
|   |                    | B [Nm]  | 8    | 25    | 40   | 80   |
| <b>Pre-setting installation</b>                 |                    |         |      |       |      |      |
| Diameter of clearance hole in the fixture       | $d_f \leq$         | [mm]    | 7    | 9     | 12   | 14   |
| Minimum thickness of fixture                    | $t_{fix} \geq$     | S [mm]  | 1    | 1     | 1    | 1    |
|   |                    | SK [mm] | 5    | 7     | 8    | 9    |
|   |                    | B [mm]  | 1    | 1     | 1    | 1    |
| <b>Through-setting installation</b>             |                    |         |      |       |      |      |
| Diameter of clearance hole in the fixture       | $d_f \leq$         | [mm]    | 9    | 12    | 14   | 18   |
| Minimum thickness of fixture <sup>1)</sup>      | $t_{fix} \geq$     | S [mm]  | 5    | 7     | 8    | 9    |
|   |                    | SK [mm] | 9    | 12    | 14   | 16   |
|   |                    | B [mm]  | 5    | 7     | 8    | 9    |

<sup>1)</sup> The minimum thickness of fixture can be reduced to the value of pre-setting installation, if the shear load at steel failure is designed with lever arm.

<sup>2)</sup> see Annex A5

**Table B5: Minimum spacings and edge distances AN BZ-IG**

| Fastener size                                |              |      | M6                     | M8  | M10 | M12 |
|--|--------------|------|------------------------|-----|-----|-----|
| Minimum thickness of concrete member         | $h_{min}$    | [mm] | 100                    | 120 | 130 | 160 |
| <b>Cracked concrete</b>                      |              |      |                        |     |     |     |
| Minimum spacing                              | $s_{min}$    | [mm] | 50                     | 60  | 70  | 80  |
|  | für $c \geq$ | [mm] | 60                     | 80  | 100 | 120 |
| Minimum edge distance                        | $c_{min}$    | [mm] | 50                     | 60  | 70  | 80  |
|  | für $s \geq$ | [mm] | 75                     | 100 | 100 | 120 |
| <b>Uncracked concrete</b>                    |              |      |                        |     |     |     |
| Minimum spacing                              | $s_{min}$    | [mm] | 50                     | 60  | 65  | 80  |
|  | für $c \geq$ | [mm] | 80                     | 100 | 120 | 160 |
| Minimum edge distance                        | $c_{min}$    | [mm] | 50                     | 60  | 70  | 100 |
|  | für $s \geq$ | [mm] | 115                    | 155 | 170 | 210 |
| <b>Fire exposure from one side</b>           |              |      |                        |     |     |     |
| Minimum spacing                              | $s_{min,fi}$ | [mm] | See normal temperature |     |     |     |
| Minimum edge distance                        | $c_{min,fi}$ | [mm] | See normal temperature |     |     |     |
| <b>Fire exposure from more than one side</b> |              |      |                        |     |     |     |
| Minimum spacing                              | $s_{min,fi}$ | [mm] | See normal temperature |     |     |     |
| Minimum edge distance                        | $c_{min,fi}$ | [mm] | $\geq 300$ mm          |     |     |     |

Intermediate values by linear interpolation.

**SIKLA Wedge Anchor AN BZ-IG**

**Intended use**

Installation parameters, minimum spacings and edge distances **AN BZ-IG**

**Annex B8**

**Table C1: Characteristic values for tension loads, AN BZ plus zinc plated, cracked concrete, static and quasi-static action**

| Fastener size   |                      | M8                                     | M10 | M12  | M16  | M20             | M24             | M27             |
|---|----------------------|--|-----|------|------|-----------------|-----------------|-----------------|
| Installation factor   | $\gamma_{inst}$ [-]  | 1,0                                    |     |      |      |                 |                 |                 |
| <b>Steel failure</b>  |                      |  |     |      |      |                 |                 |                 |
| Characteristic resistance   | $N_{Rk,s}$ [kN]      | 16                                     | 27  | 40   | 60   | 86              | 126             | 196             |
| Partial factor  | $\gamma_{Ms}$ [-]    | 1,53                                   |     | 1,5  |      | 1,6             | 1,5             |                 |
| <b>Pull-out</b>   |                      |  |     |      |      |                 |                 |                 |
| <b>Standard anchorage depth</b>                                   |                      |  |     |      |      |                 |                 |                 |
| Characteristic resistance in cracked concrete C20/25              | $N_{Rk,p}$ [kN]      | 5                                      | 9   | 16   | 25   | 36              | 44,4            | 50,3            |
| <b>Reduced anchorage depth</b>                                    |                      |  |     |      |      |                 |                 |                 |
| Characteristic resistance in cracked concrete C20/25              | $N_{Rk,p}$ [kN]      | 5                                      | 7,5 | 12,7 | 18,9 | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
| Increasing factor for $N_{Rk,p} = \psi_c \cdot N_{Rk,p} (C20/25)$ | $\psi_c$ [-]         | $\left(\frac{f_{ck}}{20}\right)^{0,5}$ |     |      |      |                 |                 |                 |
| <b>Concrete cone failure</b>                                      |                      |  |     |      |      |                 |                 |                 |
| Effective anchorage depth   | $h_{ef}$ [mm]        | 46                                     | 60  | 70   | 85   | 100             | 115             | 125             |
| Reduced anchorage depth   | $h_{ef,red}$ [mm]    | 35 <sup>2)</sup>                       | 40  | 50   | 65   | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
| Factor for cracked concrete                                       | $k_1 = k_{cr,N}$ [-] | 7,7                                    |     |      |      |                 |                 |                 |

<sup>1)</sup> No performance assessed

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate

**SIKLA Wedge Anchor AN BZ plus**

**Performance**  
Characteristic values for **tension loads, AN BZ plus zinc plated, cracked concrete, static and quasi-static action**

**Annex C1**

**Table C2: Characteristic values for tension loads, AN BZ plus A4 / HCR, cracked concrete, static and quasi-static action**

| Fastener size   |                 |      | M8                                     | M10 | M12  | M16  | M20             | M24             |
|---|-----------------|------|--|-----|------|------|-----------------|-----------------|
| Installation factor   | $\gamma_{inst}$ | [-]  | 1,0                                    |     |      |      |                 |                 |
| <b>Steel failure</b>  |                 |      |  |     |      |      |                 |                 |
| Characteristic resistance   | $N_{Rk,s}$      | [kN] | 16                                     | 27  | 40   | 64   | 108             | 110             |
| Partial factor  | $\gamma_{Ms}$   | [-]  | 1,5                                    |     |      |      | 1,68            | 1,5             |
| <b>Pull-out</b>   |                 |      |  |     |      |      |                 |                 |
| <b>Standard anchorage depth</b>                                   |                 |      |  |     |      |      |                 |                 |
| Characteristic resistance in cracked concrete C20/25              | $N_{Rk,p}$      | [kN] | 5                                      | 9   | 16   | 25   | 36              | 40              |
| <b>Reduced anchorage depth</b>                                    |                 |      |  |     |      |      |                 |                 |
| Characteristic resistance in cracked concrete C20/25              | $N_{Rk,p}$      | [kN] | 5                                      | 7,5 | 12,7 | 18,9 | - <sup>1)</sup> | - <sup>1)</sup> |
| Increasing factor for $N_{Rk,p} = \psi_c \cdot N_{Rk,p} (C20/25)$ | $\psi_c$        | [-]  | $\left(\frac{f_{ck}}{20}\right)^{0,5}$ |     |      |      |                 |                 |
| <b>Concrete cone failure</b>                                      |                 |      |  |     |      |      |                 |                 |
| Effective anchorage depth   | $h_{ef}$        | [mm] | 46                                     | 60  | 70   | 85   | 100             | 125             |
| Reduced anchorage depth   | $h_{ef,red}$    | [mm] | 35 <sup>2)</sup>                       | 40  | 50   | 65   | - <sup>1)</sup> | - <sup>1)</sup> |
| Factor for cracked concrete                                       | $k_{cr,N}$      | [-]  | 7,7                                    |     |      |      |                 |                 |

<sup>1)</sup> No performance assessed.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

**SIKLA Wedge Anchor AN BZ plus**

**Performance**

Characteristic values for **tension loads, AN BZ plus A4 / HCR, cracked concrete, static and quasi-static action**

**Annex C2**

**Table C3: Characteristic values for tension loads, AN BZ plus zinc plated, uncracked concrete, static and quasi-static action**

| Fastener size  |                       | M8                                     | M10 | M12  | M16  | M20             | M24             | M27             |
|--|-----------------------|--|-----|------|------|-----------------|-----------------|-----------------|
| Installation factor  | $\gamma_{inst}$ [-]   | 1,0                                    |     |      |      |                 |                 |                 |
| <b>Steel failure</b>   |                       |  |     |      |      |                 |                 |                 |
| Characteristic resistance  | $N_{Rk,s}$ [kN]       | 16                                     | 27  | 40   | 60   | 86              | 126             | 196             |
| Partial factor   | $\gamma_{Ms}$ [-]     | 1,53                                   |     | 1,5  |      | 1,6             | 1,5             |                 |
| <b>Pull-out</b>  |                       |  |     |      |      |                 |                 |                 |
| <b>Standard anchorage depth</b>  |                       |  |     |      |      |                 |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N_{Rk,p}$ [kN]       | 12                                     | 16  | 25   | 35   | 51              | 62,9            | 71,3            |
| <b>Reduced anchorage depth</b>   |                       |  |     |      |      |                 |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N_{Rk,p}$ [kN]       | 7,5                                    | 9   | 18   | 26,7 | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
| <b>Splitting</b>   |                       |  |     |      |      |                 |                 |                 |
| <b>Standard anchorage depth</b>  |                       |  |     |      |      |                 |                 |                 |
| <b>Splitting for standard thickness of concrete member</b> (The higher resistance of case 1 and case 2 may be applied; $C_{cr,sp}$ may be linearly interpolated for the member thickness $h_{min,2} < h < h_{min,1}$ (Case 2); $\psi_{h,sp} = 1,0$ ) |                       |  |     |      |      |                 |                 |                 |
| Standard thickness of concrete   | $h_{min,1} \geq$ [mm] | 100                                    | 120 | 140  | 170  | 200             | 230             | 250             |
| <b>Case 1</b>  |                       |  |     |      |      |                 |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N^0_{Rk,sp}$ [kN]    | 9                                      | 12  | 20   | 30   | 40              | 62,3            | 50              |
| Edge distance  | $C_{cr,sp}$ [mm]      | $1,5 h_{ef}$                           |     |      |      |                 |                 |                 |
| <b>Case 2</b>  |                       |  |     |      |      |                 |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N^0_{Rk,sp}$ [kN]    | 12                                     | 16  | 25   | 35   | 50,5            | 62,3            | 70,6            |
| Edge distance  | $C_{cr,sp}$ [mm]      | $2h_{ef}$                              |     |      |      | $2,2 h_{ef}$    | $1,5 h_{ef}$    | $2,5 h_{ef}$    |
| <b>Splitting for minimum thickness of concrete member</b>  |                       |  |     |      |      |                 |                 |                 |
| Minimum thickness of concrete  | $h_{min,2} \geq$ [mm] | 80                                     | 100 | 120  | 140  |                 |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N^0_{Rk,sp}$ [kN]    | 12                                     | 16  | 25   | 35   | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
| Edge distance  | $C_{cr,sp}$ [mm]      | $2,5h_{ef}$                            |     |      |      |                 |                 |                 |
| <b>Reduced anchorage depth</b>   |                       |  |     |      |      |                 |                 |                 |
| Minimum thickness of concrete  | $h_{min,3} \geq$ [mm] | 80                                     | 80  | 100  | 140  |                 |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N^0_{Rk,sp}$ [kN]    | 7,5                                    | 9   | 17,9 | 26,5 | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
| Edge distance  | $C_{cr,sp}$ [mm]      | 100                                    | 100 | 125  | 150  |                 |                 |                 |
| Increasing factor  | $\psi_c$ [-]          | $\left(\frac{f_{ck}}{20}\right)^{0,5}$ |     |      |      |                 |                 |                 |
| $N_{Rk,p} = \psi_o \cdot N_{Rk,p} (C20/25)$<br>$N^0_{Rk,sp} = \psi_c \cdot N^0_{Rk,sp} (C20/25)$   |                       |  |     |      |      |                 |                 |                 |
| <b>Concrete cone failure</b>   |                       |  |     |      |      |                 |                 |                 |
| Effective anchorage depth  | $h_{ef}$ [mm]         | 46                                     | 60  | 70   | 85   | 100             | 115             | 125             |
| Reduced anchorage depth  | $h_{ef,red}$ [mm]     | 35 <sup>2)</sup>                       | 40  | 50   | 65   | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
| Factor for uncracked concrete  | $k_1 = k_{ucr,N}$ [-] | 11,0                                   |     |      |      |                 |                 |                 |

<sup>1)</sup> No performance assessed.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

**SIKLA Wedge Anchor AN BZ plus**

**Performance**

Characteristic values for tension loads, AN BZ plus zinc plated, uncracked concrete, static and quasi-static action

**Annex C3**



**Table C4: Characteristic values for tension loads, AN BZ plus A4 / HCR, uncracked concrete, static and quasi-static action**

| Fastener size  |                   |      | M8                                     | M10 | M12  | M16  | M20             | M24             |
|--|-------------------|------|--|-----|------|------|-----------------|-----------------|
| Installation factor  | $\gamma_{inst}$   | [-]  | 1,0                                    |     |      |      |                 |                 |
| <b>Steel failure</b>   |                   |      |  |     |      |      |                 |                 |
| Characteristic resistance  | $N_{Rk,s}$        | [kN] | 16                                     | 27  | 40   | 64   | 108             | 110             |
| Partial factor   | $\gamma_{Ms}$     | [-]  | 1,5                                    |     |      |      | 1,68            | 1,5             |
| <b>Pull-out</b>  |                   |      |  |     |      |      |                 |                 |
| <b>Standard anchorage depth</b>  |                   |      |  |     |      |      |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N_{Rk,p}$        | [kN] | 12                                     | 16  | 25   | 35   | 51              | 71,3            |
| <b>Reduced anchorage depth</b>   |                   |      |  |     |      |      |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N_{Rk,p}$        | [kN] | 7,5                                    | 9   | 18   | 26,7 | - <sup>1)</sup> | - <sup>1)</sup> |
| <b>Splitting</b>   |                   |      |  |     |      |      |                 |                 |
| <b>Standard anchorage depth</b>  |                   |      |  |     |      |      |                 |                 |
| <u>Splitting for standard thickness of concrete member</u> (The higher resistance of case 1 and case 2 may be applied; $C_{cr,sp}$ may be linearly interpolated for the member thickness $h_{min,2} < h < h_{min,1}$ (Case 2); $\psi_{h,sp} = 1,0$ ) |                   |      |  |     |      |      |                 |                 |
| Standard thickness of concrete   | $h_{min,1} \geq$  | [mm] | 100                                    | 120 | 140  | 160  | 200             | 250             |
| <b>Case 1</b>  |                   |      |  |     |      |      |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N^0_{Rk,sp}$     | [kN] | 9                                      | 12  | 20   | 30   | 40              | - <sup>1)</sup> |
| Edge distance  | $C_{cr,sp}$       | [mm] | 1,5 $h_{ef}$                           |     |      |      |                 | - <sup>1)</sup> |
| <b>Case 2</b>  |                   |      |  |     |      |      |                 |                 |
| Characteristic resistance in uncracked concrete C20/25   | $N^0_{Rk,sp}$     | [kN] | 12                                     | 16  | 25   | 35   | 50,5            | 70,6            |
| Edge distance  | $C_{cr,sp}$       | [mm] | 115                                    | 125 | 140  | 200  | 220             | 250             |
| <u>Splitting for minimum thickness of concrete member</u>  |                   |      |  |     |      |      |                 |                 |
| Minimum thickness of concrete  | $h_{min,2} \geq$  | [mm] | 80                                     | 100 | 120  | 140  | - <sup>1)</sup> | - <sup>1)</sup> |
| Characteristic resistance in uncracked concrete C20/25   | $N^0_{Rk,sp}$     | [kN] | 12                                     | 16  | 25   | 35   |                 |                 |
| Edge distance  | $C_{cr,sp}$       | [mm] | 2,5 $h_{ef}$                           |     |      |      |                 |                 |
| <b>Reduced anchorage depth</b>   |                   |      |  |     |      |      |                 |                 |
| Minimum thickness of concrete  | $h_{min,3} \geq$  | [mm] | 80                                     | 80  | 100  | 140  | - <sup>1)</sup> | - <sup>1)</sup> |
| Characteristic resistance in uncracked concrete C20/25   | $N^0_{Rk,sp}$     | [kN] | 7,5                                    | 9   | 17,9 | 26,5 |                 |                 |
| Edge distance  | $C_{cr,sp}$       | [mm] | 100                                    | 100 | 125  | 150  |                 |                 |
| Increasing factor  | $\psi_C$          | [-]  | $\left(\frac{f_{ck}}{20}\right)^{0,5}$ |     |      |      |                 |                 |
| <b>Concrete cone failure</b>   |                   |      |  |     |      |      |                 |                 |
| Effective anchorage depth  | $h_{ef}$          | [mm] | 46                                     | 60  | 70   | 85   | 100             | 125             |
| Reduced anchorage depth  | $h_{ef,red}$      | [mm] | 35 <sup>2)</sup>                       | 40  | 50   | 65   | - <sup>1)</sup> | - <sup>1)</sup> |
| Factor for uncracked concrete  | $k_1 = k_{ucr,N}$ | [-]  | 11,0                                   |     |      |      |                 |                 |

<sup>1)</sup> No performance assessed.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

**SIKLA Wedge Anchor AN BZ plus**

**Performance**

Characteristic values for tension loads, AN BZ plus A4 / HCR, uncracked concrete, static and quasi-static action

**Annex C4**

**Table C5: Characteristic values for shear loads, AN BZ plus,  
cracked and uncracked concrete, static or quasi static action**

| Fastener size   |                         |             | M8   | M10              | M12 | M16 | M20  | M24             | M27             |                 |
|---|-------------------------|-------------|------|------------------|-----|-----|------|-----------------|-----------------|-----------------|
| Installation factor   | $\gamma_{inst}$         | [-]         | 1,0  |                  |     |     |      |                 |                 |                 |
| <b>Steel failure without lever arm, Steel zinc plated</b>       |                         |             |      |                  |     |     |      |                 |                 |                 |
| Characteristic resistance                                       | $V^0_{Rk,s}$            | [kN]        | 12,2 | 20,1             | 30  | 55  | 69   | 114             | 169,4           |                 |
| Ductility factor  | $k_7$                   | [-]         | 1,0  |                  |     |     |      |                 |                 |                 |
| Partial factor  | $\gamma_{Ms}$           | [-]         | 1,25 |                  |     |     | 1,33 | 1,25            | 1,25            |                 |
| <b>Steel failure without lever arm, Stainless steel A4, HCR</b> |                         |             |      |                  |     |     |      |                 |                 |                 |
| Characteristic resistance                                       | $V^0_{Rk,s}$            | [kN]        | 13   | 20               | 30  | 55  | 86   | 123,6           | - <sup>1)</sup> |                 |
| Ductility factor  | $k_7$                   | [-]         | 1,0  |                  |     |     |      |                 |                 |                 |
| Partial factor  | $\gamma_{Ms}$           | [-]         | 1,25 |                  |     |     | 1,4  | 1,25            |                 |                 |
| <b>Steel failure with lever arm, Steel zinc plated</b>          |                         |             |      |                  |     |     |      |                 |                 |                 |
| Characteristic bending resistance                               | $M^0_{Rk,s}$            | [Nm]        | 23   | 47               | 82  | 216 | 363  | 898             | 1331,5          |                 |
| Partial factor  | $\gamma_{Ms}$           | [-]         | 1,25 |                  |     |     | 1,33 | 1,25            | 1,25            |                 |
| <b>Steel failure with lever arm, Stainless steel A4, HCR</b>    |                         |             |      |                  |     |     |      |                 |                 |                 |
| Characteristic bending resistance                               | $M^0_{Rk,s}$            | [Nm]        | 26   | 52               | 92  | 200 | 454  | 785,4           | - <sup>1)</sup> |                 |
| Partial factor  | $\gamma_{Ms}$           | [-]         | 1,25 |                  |     |     | 1,4  | 1,25            |                 |                 |
| <b>Concrete pry-out failure</b>                                 |                         |             |      |                  |     |     |      |                 |                 |                 |
| Pry-out factor  | $k_8$                   | [-]         | 2,4  |                  |     |     | 2,8  |                 |                 |                 |
| <b>Concrete edge failure</b>                                    |                         |             |      |                  |     |     |      |                 |                 |                 |
| Effective length of fastener in shear loading with $h_{ef}$     | Steel zinc plated       | $l_f$       | [mm] | 46               | 60  | 70  | 85   | 100             | 115             | 125             |
|   | Stainless steel A4, HCR | $l_f$       | [mm] | 46               | 60  | 70  | 85   | 100             | 125             | - <sup>1)</sup> |
| Effective length of fastener in shear loading with $h_{ef,red}$ | Steel zinc plated       | $l_{f,red}$ | [mm] | 35 <sup>2)</sup> | 40  | 50  | 65   | - <sup>1)</sup> | - <sup>1)</sup> | - <sup>1)</sup> |
|   | Stainless steel A4, HCR | $l_{f,red}$ | [mm] | 35 <sup>2)</sup> | 40  | 50  | 65   |                 |                 |                 |
| Outside diameter of fastener                                    | $d_{nom}$               | [mm]        | 8    | 10               | 12  | 16  | 20   | 24              | 27              |                 |

<sup>1)</sup> No performance assessed.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

**SIKLA Wedge Anchor AN BZ plus**

**Performance**

Characteristic values for shear loads, AN BZ plus,  
cracked and uncracked concrete, static or quasi static action

**Annex C5**

**Table C6: Characteristic resistance for seismic loading, AN BZ plus,  
standard anchorage depth, performance category C1 and C2**

| Fastener size   |                                |                  | M8   | M10 | M12  | M16  | M20  |      |
|---|--------------------------------|------------------|------|-----|------|------|------|------|
| <b>Tension loads</b>  |                                |                  |      |     |      |      |      |      |
| Installation factor   |                                | $\gamma_{inst}$  | [-]  |     | 1,0  |      |      |      |
| <b>Steel failure, Steel zinc plated</b>                         |                                |                  |      |     |      |      |      |      |
| Characteristic resistance C1                                    |                                | $N_{Rk,s,eq,C1}$ | [kN] | 16  | 27   | 40   | 60   | 86   |
| Characteristic resistance C2                                    |                                | $N_{Rk,s,eq,C2}$ | [kN] | 16  | 27   | 40   | 60   | 86   |
| Partial factor  |                                | $\gamma_{Ms}$    | [-]  |     | 1,53 |      | 1,5  | 1,6  |
| <b>Steel failure, Stainless steel A4, HCR</b>                   |                                |                  |      |     |      |      |      |      |
| Characteristic resistance C1                                    |                                | $N_{Rk,s,eq,C1}$ | [kN] | 16  | 27   | 40   | 64   | 108  |
| Characteristic resistance C2                                    |                                | $N_{Rk,s,eq,C2}$ | [kN] | 16  | 27   | 40   | 64   | 108  |
| Partial factor  |                                | $\gamma_{Ms}$    | [-]  |     | 1,5  |      |      | 1,68 |
| <b>Pull-out (steel zinc plated, stainless steel A4 and HCR)</b> |                                |                  |      |     |      |      |      |      |
| Characteristic resistance C1                                    |                                | $N_{Rk,p,eq,C1}$ | [kN] | 5   | 9    | 16   | 25   | 36   |
| Characteristic resistance C2                                    |                                | $N_{Rk,p,eq,C2}$ | [kN] | 2,3 | 3,6  | 10,2 | 13,8 | 24,4 |
| <b>Shear loads</b>  |                                |                  |      |     |      |      |      |      |
| <b>Steel failure without lever arm, Steel zinc plated</b>       |                                |                  |      |     |      |      |      |      |
| Characteristic resistance C1                                    |                                | $V_{Rk,s,eq,C1}$ | [kN] | 9,3 | 20   | 27   | 44   | 69   |
| Characteristic resistance C2                                    |                                | $V_{Rk,s,eq,C2}$ | [kN] | 6,7 | 14   | 16,2 | 35,7 | 55,2 |
| Partial factor  |                                | $\gamma_{Ms}$    | [-]  |     | 1,25 |      |      | 1,33 |
| <b>Steel failure without lever arm, Stainless steel A4, HCR</b> |                                |                  |      |     |      |      |      |      |
| Characteristic resistance C1                                    |                                | $V_{Rk,s,eq,C1}$ | [kN] | 9,3 | 20   | 27   | 44   | 69   |
| Characteristic resistance C2                                    |                                | $V_{Rk,s,eq,C2}$ | [kN] | 6,7 | 14   | 16,2 | 35,7 | 55,2 |
| Partial factor  |                                | $\gamma_{Ms}$    | [-]  |     | 1,25 |      |      | 1,4  |
| Factor for annular gap  | without filling of annular gap | $\alpha_{gap}$   | [-]  |     | 0,5  |      |      |      |
|   | with filling of annular gap    | $\alpha_{gap}$   | [-]  |     | 1,0  |      |      |      |

**SIKLA Wedge Anchor AN BZ plus**

**Performance**  
Characteristic resistance for **seismic loading**, AN BZ plus,  
**standard anchorage depth**, performance category **C1** and **C2**

**Annex C6**

**Table C7: Characteristic values for tension and shear load under fire exposure, AN BZ plus, standard anchorage depth, cracked and uncracked concrete C20/25 to C50/60**

| Fastener size                          |      | M8              | M10  | M12 | M16 | M20  | M24  | M27  |       |      |
|--|------|-----------------|------|-----|-----|------|------|------|-------|------|
| <b>Tension load</b>                    |      |                 |      |     |     |      |      |      |       |      |
| <b>Steel failure</b>                   |      |                 |      |     |     |      |      |      |       |      |
| <b>Steel, zinc plated</b>              |      |                 |      |     |     |      |      |      |       |      |
| Characteristic resistance              | R30  | $N_{Rk,s,fi}$   | [kN] | 1,5 | 2,6 | 4,1  | 7,7  | 9,4  | 13,6  | 17,6 |
|  | R60  |                 |      | 1,1 | 1,9 | 3,0  | 5,6  | 8,2  | 11,8  | 15,3 |
|  | R90  |                 |      | 0,8 | 1,4 | 2,4  | 4,4  | 6,9  | 10,0  | 13,0 |
|  | R120 |                 |      | 0,7 | 1,2 | 2,2  | 4,0  | 6,3  | 9,1   | 11,8 |
| <b>Stainless steel A4, HCR</b>         |      |                 |      |     |     |      |      |      |       |      |
| Characteristic resistance              | R30  | $N_{Rk,s,fi}$   | [kN] | 3,8 | 6,9 | 12,7 | 23,7 | 33,5 | 48,2  | -1)  |
|  | R60  |                 |      | 2,9 | 5,3 | 9,4  | 17,6 | 25,0 | 35,9  |      |
|  | R90  |                 |      | 2,0 | 3,6 | 6,1  | 11,5 | 16,4 | 23,6  |      |
|  | R120 |                 |      | 1,6 | 2,8 | 4,5  | 8,4  | 12,1 | 17,4  |      |
| <b>Shear load</b>                      |      |                 |      |     |     |      |      |      |       |      |
| <b>Steel failure without lever arm</b> |      |                 |      |     |     |      |      |      |       |      |
| <b>Steel, zinc plated</b>              |      |                 |      |     |     |      |      |      |       |      |
| Characteristic resistance              | R30  | $V_{Rk,s,fi}$   | [kN] | 1,6 | 2,6 | 4,1  | 7,7  | 11   | 16    | 20,6 |
|  | R60  |                 |      | 1,5 | 2,5 | 3,6  | 6,8  | 11   | 15    | 19,8 |
|  | R90  |                 |      | 1,2 | 2,1 | 3,5  | 6,5  | 10   | 15    | 19,0 |
|  | R120 |                 |      | 1,0 | 2,0 | 3,4  | 6,4  | 10   | 14    | 18,6 |
| <b>Stainless steel A4, HCR</b>         |      |                 |      |     |     |      |      |      |       |      |
| Characteristic resistance              | R30  | $V_{Rk,s,fi}$   | [kN] | 3,8 | 6,9 | 12,7 | 23,7 | 33,5 | 48,2  | -1)  |
|  | R60  |                 |      | 2,9 | 5,3 | 9,4  | 17,6 | 25,0 | 35,9  |      |
|  | R90  |                 |      | 2,0 | 3,6 | 6,1  | 11,5 | 16,4 | 23,6  |      |
|  | R120 |                 |      | 1,6 | 2,8 | 4,5  | 8,4  | 12,1 | 17,4  |      |
| <b>Steel failure with lever arm</b>    |      |                 |      |     |     |      |      |      |       |      |
| <b>Steel, zinc plated</b>              |      |                 |      |     |     |      |      |      |       |      |
| Characteristic resistance              | R30  | $M^0_{Rk,s,fi}$ | [Nm] | 1,7 | 3,3 | 6,4  | 16,3 | 29   | 50    | 75   |
|  | R60  |                 |      | 1,6 | 3,2 | 5,6  | 14   | 28   | 48    | 72   |
|  | R90  |                 |      | 1,2 | 2,7 | 5,4  | 14   | 27   | 47    | 69   |
|  | R120 |                 |      | 1,1 | 2,5 | 5,3  | 13   | 26   | 46    | 68   |
| <b>Stainless steel A4, HCR</b>         |      |                 |      |     |     |      |      |      |       |      |
| Characteristic resistance              | R30  | $M^0_{Rk,s,fi}$ | [Nm] | 3,8 | 9,0 | 19,7 | 50,1 | 88,8 | 153,5 | -1)  |
|  | R60  |                 |      | 2,9 | 6,8 | 14,6 | 37,2 | 66,1 | 114,3 |      |
|  | R90  |                 |      | 2,1 | 4,7 | 9,5  | 24,2 | 43,4 | 75,1  |      |
|  | R120 |                 |      | 1,6 | 3,6 | 7,0  | 17,8 | 32,1 | 55,5  |      |

<sup>1)</sup> No performance assessed

**SIKLA Wedge Anchor AN BZ plus**

**Performance**

Characteristic values for tension and shear load under fire exposure, AN BZ plus, standard anchorage depth, cracked and uncracked concrete C20/25 to C50/60

**Annex C7**

**Table C8: Characteristic values for tension and shear load under fire exposure, AN BZ plus, reduced anchorage depth, cracked and uncracked concrete C20/25 to C50/60**

| Fastener size                          |      | M8              | M10  | M12 | M16 |      |      |
|--|------|-----------------|------|-----|-----|------|------|
| <b>Tension load</b>                    |      |                 |      |     |     |      |      |
| <b>Steel failure</b>                   |      |                 |      |     |     |      |      |
| <b>Steel, zinc plated</b>              |      |                 |      |     |     |      |      |
| Characteristic resistance              | R30  | $N_{Rk,s,fi}$   | [kN] | 1,5 | 2,6 | 4,1  | 7,7  |
|  | R60  |                 |      | 1,1 | 1,9 | 3,0  | 5,6  |
|  | R90  |                 |      | 0,8 | 1,3 | 1,9  | 3,5  |
|  | R120 |                 |      | 0,6 | 1,0 | 1,3  | 2,5  |
| <b>Stainless steel A4, HCR</b>         |      |                 |      |     |     |      |      |
| Characteristic resistance              | R30  | $N_{Rk,s,fi}$   | [kN] | 3,2 | 6,9 | 12,7 | 23,7 |
|  | R60  |                 |      | 2,5 | 5,3 | 9,4  | 17,6 |
|  | R90  |                 |      | 1,9 | 3,6 | 6,1  | 11,5 |
|  | R120 |                 |      | 1,6 | 2,8 | 4,5  | 8,4  |
| <b>Shear load</b>                      |      |                 |      |     |     |      |      |
| <b>Steel failure without lever arm</b> |      |                 |      |     |     |      |      |
| <b>Steel, zinc plated</b>              |      |                 |      |     |     |      |      |
| Characteristic resistance              | R30  | $V_{Rk,s,fi}$   | [kN] | 1,5 | 2,6 | 4,1  | 7,7  |
|  | R60  |                 |      | 1,1 | 1,9 | 3,0  | 5,6  |
|  | R90  |                 |      | 0,8 | 1,3 | 1,9  | 3,5  |
|  | R120 |                 |      | 0,6 | 1,0 | 1,3  | 2,5  |
| <b>Stainless steel A4, HCR</b>         |      |                 |      |     |     |      |      |
| Characteristic resistance              | R30  | $V_{Rk,s,fi}$   | [kN] | 3,2 | 6,9 | 12,7 | 23,7 |
|  | R60  |                 |      | 2,5 | 5,3 | 9,4  | 17,6 |
|  | R90  |                 |      | 1,9 | 3,6 | 6,1  | 11,5 |
|  | R120 |                 |      | 1,6 | 2,8 | 4,5  | 8,4  |
| <b>Steel failure with lever arm</b>    |      |                 |      |     |     |      |      |
| <b>Steel, zinc plated</b>              |      |                 |      |     |     |      |      |
| Characteristic resistance              | R30  | $M^0_{Rk,s,fi}$ | [Nm] | 1,5 | 3,3 | 6,4  | 16,3 |
|  | R60  |                 |      | 1,2 | 2,5 | 4,7  | 11,9 |
|  | R90  |                 |      | 0,8 | 1,7 | 3,0  | 7,5  |
|  | R120 |                 |      | 0,6 | 1,2 | 2,1  | 5,3  |
| <b>Stainless steel A4, HCR</b>         |      |                 |      |     |     |      |      |
| Characteristic resistance              | R30  | $M^0_{Rk,s,fi}$ | [Nm] | 3,2 | 8,9 | 19,7 | 50,1 |
|  | R60  |                 |      | 2,6 | 6,8 | 14,6 | 37,2 |
|  | R90  |                 |      | 2,0 | 4,7 | 9,5  | 24,2 |
|  | R120 |                 |      | 1,6 | 3,6 | 7,0  | 17,8 |

**SIKLA Wedge Anchor AN BZ plus**

**Performance**

Characteristic values for tension and shear load under fire exposure, AN BZ plus, reduced anchorage depth, cracked and uncracked concrete C20/25 to C50/60

**Annex C8**

**Table C9: Displacements under tension load, AN BZ plus**

| Fastener size                                       |                       |      | M8  | M10  | M12  | M16  | M20  | M24  | M27 |
|---|-----------------------|------|-----|------|------|------|------|------|-----|
| <b>Standard anchorage depth</b>                     |                       |      |     |      |      |      |      |      |     |
| <b>Steel zinc plated</b>                            |                       |      |     |      |      |      |      |      |     |
| Tension load in cracked concrete                    | N                     | [kN] | 2,4 | 4,3  | 7,6  | 11,9 | 17,1 | 21,1 | 24  |
| Displacement  | $\delta_{N0}$         | [mm] | 0,6 | 1,0  | 0,4  | 1,0  | 0,9  | 0,7  | 0,9 |
|   | $\delta_{N\infty}$    | [mm] | 1,4 | 1,2  | 1,4  | 1,3  | 1,0  | 1,2  | 1,4 |
| Tension load in uncracked concrete                  | N                     | [kN] | 5,7 | 7,6  | 11,9 | 16,7 | 23,8 | 29,6 | 34  |
| Displacement  | $\delta_{N0}$         | [mm] | 0,4 | 0,5  | 0,7  | 0,3  | 0,4  | 0,5  | 0,3 |
|   | $\delta_{N\infty}$    | [mm] | 0,8 |      | 1,4  | 0,8  |      | 1,4  |     |
| <b>Displacements under seismic tension loads C2</b> |                       |      |     |      |      |      |      |      |     |
| Displacements for DLS                               | $\delta_{N,eq,(DLS)}$ | [mm] | 2,3 | 4,1  | 4,9  | 3,6  | 5,1  | -1)  | -1) |
| Displacements for ULS                               | $\delta_{N,eq,(ULS)}$ | [mm] | 8,2 | 13,8 | 15,7 | 9,5  | 15,2 | -1)  | -1) |
| <b>Stainless steel A4, HCR</b>                      |                       |      |     |      |      |      |      |      |     |
| Tension load in cracked concrete                    | N                     | [kN] | 2,4 | 4,3  | 7,6  | 11,9 | 17,1 | 19,0 | -1) |
| Displacement  | $\delta_{N0}$         | [mm] | 0,7 | 1,8  | 0,4  | 0,7  | 0,9  | 0,5  |     |
|   | $\delta_{N\infty}$    | [mm] | 1,2 | 1,4  | 1,4  | 1,4  | 1,0  | 1,8  |     |
| Tension load in uncracked concrete                  | N                     | [kN] | 5,8 | 7,6  | 11,9 | 16,7 | 23,8 | 33,5 | -1) |
| Displacement  | $\delta_{N0}$         | [mm] | 0,6 | 0,5  | 0,7  | 0,2  | 0,4  | 0,5  |     |
|   | $\delta_{N\infty}$    | [mm] | 1,2 | 1,0  | 1,4  | 0,4  | 0,8  | 1,1  |     |
| <b>Displacements under seismic tension loads C2</b> |                       |      |     |      |      |      |      |      |     |
| Displacements for DLS                               | $\delta_{N,eq,(DLS)}$ | [mm] | 2,3 | 4,1  | 4,9  | 3,6  | 5,1  | -1)  | -1) |
| Displacements for ULS                               | $\delta_{N,eq,(ULS)}$ | [mm] | 8,2 | 13,8 | 15,7 | 9,5  | 15,2 | -1)  | -1) |
| <b>Reduced anchorage depth</b>                      |                       |      |     |      |      |      |      |      |     |
| <b>Steel zinc plated, stainless steel A4, HCR</b>   |                       |      |     |      |      |      |      |      |     |
| Tension load in cracked concrete                    | N                     | [kN] | 2,4 | 3,6  | 6,1  | 9,0  | -1)  | -1)  | -1) |
| Displacement  | $\delta_{N0}$         | [mm] | 0,8 | 0,7  | 0,5  | 1,0  |      |      |     |
|   | $\delta_{N\infty}$    | [mm] | 1,2 | 1,0  | 0,8  | 1,1  |      |      |     |
| Tension load in uncracked concrete                  | N                     | [kN] | 3,7 | 4,3  | 8,5  | 12,6 | -1)  | -1)  | -1) |
| Displacement  | $\delta_{N0}$         | [mm] | 0,1 | 0,2  | 0,2  | 0,2  |      |      |     |
|   | $\delta_{N\infty}$    | [mm] | 0,7 | 0,7  | 0,7  | 0,7  |      |      |     |

<sup>1)</sup> No performance assessed

**SIKLA Wedge Anchor AN BZ plus**

**Performance**  
Displacements under tension load

**Annex C9**

**Table C10: Displacements under shear load, AN BZ plus**

| Fastener size                                     |                      |      | M8  | M10  | M12  | M16  | M20  | M24  | M27  |
|---|----------------------|------|-----|------|------|------|------|------|------|
| <b>Standard anchorage depth</b>                   |                      |      |     |      |      |      |      |      |      |
| <b>Steel zinc plated</b>                          |                      |      |     |      |      |      |      |      |      |
| Shear load in cracked and uncracked concrete      | V                    | [kN] | 6,9 | 11,4 | 17,1 | 31,4 | 36,8 | 64,9 | 96,8 |
| Displacement                                      | $\delta_{V0}$        | [mm] | 2,0 | 3,2  | 3,6  | 3,5  | 1,8  | 3,5  | 3,6  |
|   | $\delta_{V\infty}$   | [mm] | 3,0 | 4,7  | 5,5  | 5,3  | 2,7  | 5,3  | 5,4  |
| <b>Displacements under seismic shear loads C2</b> |                      |      |     |      |      |      |      |      |      |
| Displacements for DLS                             | $\delta_{V,eq(DLS)}$ | [mm] | 3,0 | 2,7  | 3,5  | 4,3  | 4,7  | -1)  | -1)  |
| Displacements for ULS                             | $\delta_{V,eq(ULS)}$ | [mm] | 5,9 | 5,3  | 9,5  | 9,6  | 10,1 |      |      |
| <b>Stainless steel A4, HCR</b>                    |                      |      |     |      |      |      |      |      |      |
| Shear load in cracked and uncracked concrete      | V                    | [kN] | 7,3 | 11,4 | 17,1 | 31,4 | 43,8 | 70,6 | -1)  |
| Displacement                                      | $\delta_{V0}$        | [mm] | 1,9 | 2,4  | 4,0  | 4,3  | 2,9  | 2,8  |      |
|   | $\delta_{V\infty}$   | [mm] | 2,9 | 3,6  | 5,9  | 6,4  | 4,3  | 4,2  |      |
| <b>Displacements under seismic shear loads C2</b> |                      |      |     |      |      |      |      |      |      |
| Displacements for DLS                             | $\delta_{V,eq(DLS)}$ | [mm] | 3,0 | 2,7  | 3,5  | 4,3  | 4,7  | -1)  | -1)  |
| Displacements for ULS                             | $\delta_{V,eq(ULS)}$ | [mm] | 5,9 | 5,3  | 9,5  | 9,6  | 10,1 |      |      |
| <b>Reduced anchorage depth</b>                    |                      |      |     |      |      |      |      |      |      |
| <b>Steel zinc plated</b>                          |                      |      |     |      |      |      |      |      |      |
| Shear load in cracked and uncracked concrete      | V                    | [kN] | 6,9 | 11,4 | 17,1 | 31,4 | -1)  | -1)  | -1)  |
| Displacement                                      | $\delta_{V0}$        | [mm] | 2,0 | 3,2  | 3,6  | 3,5  |      |      |      |
|   | $\delta_{V\infty}$   | [mm] | 3,0 | 4,7  | 5,5  | 5,3  |      |      |      |
| <b>Stainless steel A4, HCR</b>                    |                      |      |     |      |      |      |      |      |      |
| Shear load in cracked and uncracked concrete      | V                    | [kN] | 7,3 | 11,4 | 17,1 | 31,4 | -1)  | -1)  | -1)  |
| Displacement                                      | $\delta_{V0}$        | [mm] | 1,9 | 2,4  | 4,0  | 4,3  |      |      |      |
|   | $\delta_{V\infty}$   | [mm] | 2,9 | 3,6  | 5,9  | 6,4  |      |      |      |

<sup>1)</sup> No performance assessed

**SIKLA Wedge Anchor AN BZ plus**

**Performance**  
Displacements under shear load

**Annex C10**

**Table C11: Characteristic values for tension loads, AN BZ-IG, cracked concrete, static and quasi-static action**

| Fastener size   |                  |      | M6                                     | M8   | M10  | M12  |
|---|------------------|------|--|------|------|------|
| Installation factor   | $\gamma_{inst}$  | [-]  | 1,2                                    |      |      |      |
| <b>Steel failure</b>  |                  |      |  |      |      |      |
| Characteristic resistance, steel zinc plated                      | $N_{Rk,s}$       | [kN] | 16,1                                   | 22,6 | 26,0 | 56,6 |
| Partial factor  | $\gamma_{Ms}$    | [-]  | 1,5                                    |      |      |      |
| Characteristic resistance, stainless steel A4, HCR                | $N_{Rk,s}$       | [kN] | 14,1                                   | 25,6 | 35,8 | 59,0 |
|   | $\gamma_{Ms}$    | [-]  | 1,87                                   |      |      |      |
| <b>Pull-out failure</b>   |                  |      |  |      |      |      |
| Characteristic resistance in cracked concrete C20/25              | $N_{Rk,p}$       | [kN] | 5                                      | 9    | 12   | 20   |
| Increasing factor for $N_{Rk,p} = \psi_c \cdot N_{Rk,p} (C20/25)$ | $\psi_c$         | [-]  | $\left(\frac{f_{ck}}{20}\right)^{0,5}$ |      |      |      |
| <b>Concrete cone failure</b>                                      |                  |      |  |      |      |      |
| Effective anchorage depth   | $h_{ef}$         | [mm] | 45                                     | 58   | 65   | 80   |
| Factor for cracked concrete                                       | $k_1 = k_{cr,N}$ | [-]  | 7,7                                    |      |      |      |

**SIKLA Wedge Anchor AN BZ-IG**

**Performance**  
Characteristic values for tension loads, AN BZ-IG, cracked concrete, static and quasi-static action

**Annex C11**



**Table C12: Characteristic values for tension loads, AN BZ-IG, uncracked concrete, static and quasi-static action**

| Fastener size   |                   |      | M6                                     | M8   | M10  | M12  |
|---|-------------------|------|--|------|------|------|
| Installation factor   | $\gamma_{inst}$   | [-]  | 1,2                                    |      |      |      |
| <b>Steel failure</b>  |                   |      |  |      |      |      |
| Characteristic resistance, steel zinc plated  | $N_{RK,s}$        | [kN] | 16,1                                   | 22,6 | 26,0 | 56,6 |
| Partial factor  | $\gamma_{Ms}$     | [-]  | 1,5                                    |      |      |      |
| Characteristic resistance, stainless steel A4, HCR  | $N_{RK,s}$        | [kN] | 14,1                                   | 25,6 | 35,8 | 59,0 |
| Partial factor  | $\gamma_{Ms}$     | [-]  | 1,87                                   |      |      |      |
| <b>Pull-out</b>   |                   |      |  |      |      |      |
| Characteristic resistance in uncracked concrete C20/25  | $N_{RK,p}$        | [kN] | 12                                     | 16   | 20   | 30   |
| <b>Splitting</b> (the higher resistance of Case 1 and Case 2 may be applied)  |                   |      |  |      |      |      |
| Minimum thickness of concrete member  | $h_{min}$         | [mm] | 100                                    | 120  | 130  | 160  |
| <b>Case 1</b>   |                   |      |  |      |      |      |
| Characteristic resistance in uncracked concrete C20/25  | $N^0_{RK,sp}$     | [kN] | 9                                      | 12   | 16   | 25   |
| Edge distance   | $c_{cr,sp}$       | [mm] | 1,5 $h_{ef}$                           |      |      |      |
| <b>Case 2</b>   |                   |      |  |      |      |      |
| Characteristic resistance in uncracked concrete C20/25  | $N^0_{RK,sp}$     | [kN] | 12                                     | 16   | 20   | 30   |
| Edge distance   | $c_{cr,sp}$       | [mm] | 2,5 $h_{ef}$                           |      |      |      |
| Increasing factor for<br>$N_{RK,p} = \psi_c \cdot N_{RK,p}$ (C20/25)<br>$N^0_{RK,sp} = \psi_c \cdot N^0_{RK,sp}$ (C20/25) | $\psi_c$          | [-]  | $\left(\frac{f_{ck}}{20}\right)^{0,5}$ |      |      |      |
| <b>Concrete cone failure</b>  |                   |      |  |      |      |      |
| Effective anchorage depth   | $h_{ef}$          | [mm] | 45                                     | 58   | 65   | 80   |
| Factor for uncracked concrete   | $k_1 = k_{ucr,N}$ | [-]  | 11,0                                   |      |      |      |

**SIKLA Wedge Anchor AN BZ-IG**

**Performance**  
Characteristic values for tension loads, AN BZ-IG, uncracked concrete, static and quasi-static action

**Annex C12**

**Table C13: Characteristic values for shear loads, AN BZ-IG,  
cracked and uncracked concrete, static and quasi-static action**

| Fastener size  |                     | M6   | M8   | M10  | M12   |
|--|---------------------|------|------|------|-------|
| Installation factor  | $\gamma_{inst}$ [-] | 1,0  |      |      |       |
| <b>BZ-IG, steel zinc plated</b>                                      |                     |      |      |      |       |
| <b>Steel failure without lever arm, pre-setting installation</b>     |                     |      |      |      |       |
| Characteristic resistance  | $V_{RK,s}^0$ [kN]   | 5,8  | 6,9  | 10,4 | 25,8  |
| <b>Steel failure without lever arm, through-setting installation</b> |                     |      |      |      |       |
| Characteristic resistance  | $V_{RK,s}^0$ [kN]   | 5,1  | 7,6  | 10,8 | 24,3  |
| <b>Steel failure with lever arm, pre-setting installation</b>        |                     |      |      |      |       |
| Characteristic bending resistance                                    | $M_{RK,s}^0$ [Nm]   | 12,2 | 30,0 | 59,8 | 104,6 |
| <b>Steel failure with lever arm, through-setting installation</b>    |                     |      |      |      |       |
| Characteristic bending resistance                                    | $M_{RK,s}^0$ [Nm]   | 36,0 | 53,2 | 76,0 | 207   |
| Partial factor for $V_{RK,s}$ and $M_{RK,s}^0$                       | $\gamma_{Ms}$ [-]   | 1,25 |      |      |       |
| Ductility factor   | $k_7$ [-]           | 1,0  |      |      |       |
| <b>BZ-IG, stainless steel A4, HCR</b>                                |                     |      |      |      |       |
| <b>Steel failure without lever arm, pre-setting installation</b>     |                     |      |      |      |       |
| Characteristic resistance  | $V_{RK,s}^0$ [kN]   | 5,7  | 9,2  | 10,6 | 23,6  |
| Partial factor   | $\gamma_{Ms}$ [-]   | 1,25 |      |      |       |
| <b>Steel failure without lever arm, through-setting installation</b> |                     |      |      |      |       |
| Characteristic resistance  | $V_{RK,s}^0$ [kN]   | 7,3  | 7,6  | 9,7  | 29,6  |
| Partial factor   | $\gamma_{Ms}$ [-]   | 1,25 |      |      |       |
| <b>Steel failure with lever arm, pre-setting installation</b>        |                     |      |      |      |       |
| Characteristic bending resistance                                    | $M_{RK,s}^0$ [Nm]   | 10,7 | 26,2 | 52,3 | 91,6  |
| Partial factor   | $\gamma_{Ms}$ [-]   | 1,56 |      |      |       |
| <b>Steel failure with lever arm, through-setting installation</b>    |                     |      |      |      |       |
| Characteristic bending resistance                                    | $M_{RK,s}^0$ [Nm]   | 28,2 | 44,3 | 69,9 | 191,2 |
| Partial factor   | $\gamma_{Ms}$ [-]   | 1,25 |      |      |       |
| Ductility factor   | $k_7$ [-]           | 1,0  |      |      |       |
| <b>Concrete pry-out failure</b>                                      |                     |      |      |      |       |
| Pry-out factor   | $k_8$ [-]           | 1,5  | 1,5  | 2,0  | 2,0   |
| <b>Concrete edge failure</b>   |                     |      |      |      |       |
| Effective length of fastener in shear loading                        | $l_f$ [mm]          | 45   | 58   | 65   | 80    |
| Effective diameter of fastener                                       | $d_{nom}$ [mm]      | 8    | 10   | 12   | 16    |

**SIKLA Wedge Anchor AN BZ-IG**

**Performance**  
Characteristic values for shear loads, AN BZ-IG,  
cracked and uncracked concrete, static and quasi-static action

**Annex C13**

**Table C14:** Characteristic values for **tension** and **shear load** under **fire exposure**, **AN BZ-IG**, cracked and uncracked concrete C20/25 to C50/60

| Fastener size                          |      | M6                   | M8  | M10 | M12  |      |
|--|------|----------------------|-----|-----|------|------|
| <b>Tension load</b>                    |      |                      |     |     |      |      |
| <b>Steel failure</b>                   |      |                      |     |     |      |      |
| <b>Steel zinc plated</b>               |      |                      |     |     |      |      |
| Characteristic resistance              | R30  | $N_{Rk,s,fi}$ [kN]   | 0,7 | 1,4 | 2,5  | 3,7  |
|  | R60  |                      | 0,6 | 1,2 | 2,0  | 2,9  |
|  | R90  |                      | 0,5 | 0,9 | 1,5  | 2,2  |
|  | R120 |                      | 0,4 | 0,8 | 1,3  | 1,8  |
| <b>Stainless steel A4, HCR</b>         |      |                      |     |     |      |      |
| Characteristic resistance              | R30  | $N_{Rk,s,fi}$ [kN]   | 2,9 | 5,4 | 8,7  | 12,6 |
|  | R60  |                      | 1,9 | 3,8 | 6,3  | 9,2  |
|  | R90  |                      | 1,0 | 2,1 | 3,9  | 5,7  |
|  | R120 |                      | 0,5 | 1,3 | 2,7  | 4,0  |
| <b>Shear load</b>                      |      |                      |     |     |      |      |
| <b>Steel failure without lever arm</b> |      |                      |     |     |      |      |
| <b>Steel zinc plated</b>               |      |                      |     |     |      |      |
| Characteristic resistance              | R30  | $V_{Rk,s,fi}$ [kN]   | 0,7 | 1,4 | 2,5  | 3,7  |
|  | R60  |                      | 0,6 | 1,2 | 2,0  | 2,9  |
|  | R90  |                      | 0,5 | 0,9 | 1,5  | 2,2  |
|  | R120 |                      | 0,4 | 0,8 | 1,3  | 1,8  |
| <b>Stainless steel A4, HCR</b>         |      |                      |     |     |      |      |
| Characteristic resistance              | R30  | $V_{Rk,s,fi}$ [kN]   | 2,9 | 5,4 | 8,7  | 12,6 |
|  | R60  |                      | 1,9 | 3,8 | 6,3  | 9,2  |
|  | R90  |                      | 1,0 | 2,1 | 3,9  | 5,7  |
|  | R120 |                      | 0,5 | 1,3 | 2,7  | 4,0  |
| <b>Steel failure with lever arm</b>    |      |                      |     |     |      |      |
| <b>Steel zinc plated</b>               |      |                      |     |     |      |      |
| Characteristic resistance              | R30  | $M^0_{Rk,s,fi}$ [Nm] | 0,5 | 1,4 | 3,3  | 5,7  |
|  | R60  |                      | 0,4 | 1,2 | 2,6  | 4,6  |
|  | R90  |                      | 0,4 | 0,9 | 2,0  | 3,4  |
|  | R120 |                      | 0,3 | 0,8 | 1,6  | 2,8  |
| <b>Stainless steel A4, HCR</b>         |      |                      |     |     |      |      |
| Characteristic resistance              | R30  | $M^0_{Rk,s,fi}$ [Nm] | 2,2 | 5,5 | 11,2 | 19,6 |
|  | R60  |                      | 1,5 | 3,9 | 8,1  | 14,3 |
|  | R90  |                      | 0,7 | 2,2 | 5,1  | 8,9  |
|  | R120 |                      | 0,4 | 1,3 | 3,5  | 6,2  |

**SIKLA Wedge Anchor AN BZ-IG**

**Performance**

Characteristic values for **tension** and **shear loads** under **fire exposure**, **AN BZ-IG**  
cracked and uncracked concrete C20/25 to C50/60

**Annex C14**

**Table C15: Displacements under tension load, AN BZ-IG**

| Fastener size                      |                    |      | M6  | M8  | M10 | M12  |
|------------------------------------|--------------------|------|-----|-----|-----|------|
| Tension load in cracked concrete   | N                  | [kN] | 2,0 | 3,6 | 4,8 | 8,0  |
| Displacements                      | $\delta_{N0}$      | [mm] | 0,6 | 0,6 | 0,8 | 1,0  |
|                                    | $\delta_{N\infty}$ | [mm] | 0,8 | 0,8 | 1,2 | 1,4  |
| Tension load in uncracked concrete | N                  | [kN] | 4,8 | 6,4 | 8,0 | 12,0 |
| Displacements                      | $\delta_{N0}$      | [mm] | 0,4 | 0,5 | 0,7 | 0,8  |
|                                    | $\delta_{N\infty}$ | [mm] | 0,8 | 0,8 | 1,2 | 1,4  |

**Table C16: Displacements under shear load, AN BZ-IG**

| Fastener size                                |                    |      | M6  | M8  | M10 | M12  |
|--|--------------------|------|-----|-----|-----|------|
| Shear load in cracked and uncracked concrete | V                  | [kN] | 4,2 | 5,3 | 6,2 | 16,9 |
| Displacements                                | $\delta_{V0}$      | [mm] | 2,8 | 2,9 | 2,5 | 3,6  |
|  | $\delta_{V\infty}$ | [mm] | 4,2 | 4,4 | 3,8 | 5,3  |

**SIKLA Wedge Anchor AN BZ-IG**

**Performance**  
Displacements under tension load and under shear load **AN BZ-IG**

**Annex C15**